

SERIES G2040



L10-G2040-40W

- Ⓟ 40W
- 💡 4000LM
- 🛡️ IP65
- 🔋 4 H/BATTERY
- 🕒 3-4H

SIZE & WEIGHT

232*212*365mm & 3110g

BEAM ANGLE

60 Degree

CCT

Optional

ACCESSORY

AC 100-240V input,DC 25.2V,2A output charger

BATTERY

capacity of each battery: 22.2V ,4.4Ah or 5.2Ah

WORKING MODE

100%-50%-off

BATTERY INDICATOR

5 levels indicator
green/green/green/amber/red

BATTERY PROTECTION

over-charging and over-discharging protection and high temperature protection(70 ℃).



L10-G2040-20W

- Ⓟ 20W
- 💡 2000LM
- 🛡️ IP65
- 🔋 4 H/BATTERY
- 🕒 7.5H/BATTERY

SIZE & WEIGHT

232*212*365mm & 3110g

BEAM ANGLE

60 Degree

CCT

Optional

ACCESSORY

AC 100-240V input,DC 25.2V,2A output charger

BATTERY

capacity of each battery: 22.2V ,4.4Ah or 5.2Ah

WORKING MODE

100%-50%-off

BATTERY INDICATOR

5 levels indicator
green/green/green/amber/red

BATTERY PROTECTION

over-charging and over-discharging protection and high temperature protection(70 ℃).

